

D.1.1.5-5 PODRUŽNÁ TLAKOVÁ STOKA - TABULKA

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
TD	0,16000	112	92,0	1				
	0,27080	111	58,8	1				
	0,27400	195	53,7	1				
	0,68000	125	7,7	1				
	0,79180	126	31,1	1				
	0,85140	127	25,0	1				
	0,94840	128	2,0					zaslepeno
	1,06200	129	46,2	1				
	1,07500	131	46,0	1				
	1,11900	130	15,8	1				
	1,15600	132	41,4	1				
	1,19300	134	28,6	1				
	1,29230	208	23,3	1				
	1,34600	202	5,6	1				
	1,38000	136	2,0	1				
	1,40600	137	28,7	1				
	1,43300	216	23,7	1				
	1,55150	95	21,8	1				
	1,55200	94	21,8	1				
	1,61180	141	23,0	1				
	1,65880	143	20,4	1				
	1,66330	87	34,6	1				
	1,66380	86	29,2	1				
	1,71700	144	11,7	1				
	1,85100	p.č.717/2			5,0	1		U Houslíček
	1,91900	148	33,5	1				
	1,93630	215	17,3	1				
	1,99360	207	18,8	1				
	2,01700	204	26,6	1				
	2,04200	149	139,4	1				
	2,08000	150	27,0	1				
	2,08500	151	65,0	1				
	2,09300	81	25,0	1				
	2,14300	p.č.4205	1,5	1				rozest.RD
	2,18800	80	10,6	1				
	2,20930	79	2,5	1				
	2,23180	78	13,5	1				
	2,15400	77	6,6	1				
	2,35070	75	64,5	1				
	2,35770	213	5,0	1				
	2,37000	154	12,0	1				
	2,39220	74	32,0	1				
	2,43100	35	42,8	1				
	2,43650	156	2,0	1				
celkem			1239,7	42	5,0	1		
T1	0,06920	116	47,0	1				

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
	0,09130	22	32,6	1				
	0,10480	225	74,0	1				
	0,12500	118	6,8	1				
	0,15800	119	11,2	1				
	0,37000	198	24,0	1				
	0,38000	120	25,7	1				
celkem			221,3	7				
T1-1	0,04680	115	7,2	1				
	0,04800	114	2,5	1				
	0,13400	196	51,5	1				
	0,13450	210	56,3	1				
	0,13500	122	58,0	1				
	0,13550	121	53,7	1				
celkem			229,2	6				
T1-2	0,02950	123	122,8	1				
celkem			122,8	1				
T2	0,11100	110	17,9	1				
	0,13550	109	40,7	1				
	0,16850	106	33,3	1				
	0,23600	105	20,8	1				
	0,32350	104	5,3	1				
	0,45630	103	74,5	1				
	0,49500	102	25,3	1				
	0,56900	101	9,0	1				
	0,59600	100	44,2	1				
	0,67200	133	57,0	1				
	0,71400	99	13,0	1				
	0,74470	211	20,0	1				
	0,90000	96	25,7	1				
	0,19100	97	17,2	1				
	0,95820	199	19,7	1				
	1,02600	93	59,2	1				
	1,07300	91	24,3	1				
celkem			507,1	17				
T2-1	0,11500	108	38,0	1				
celkem			38,0	1				
T2-2	0,05700	209	1,2	1				
	0,05750	98	14,0	1				
celkem			15,2	2				
T3	0,03050	88	36,2	1				
	0,09300	89	7,3	1				
	0,15620	85	50,0	1				
	0,18470	90	12,7	1				
	0,24520	201	106,0	1				
	0,24570	84	82,6	1				
	0,26400	82	117,0	1				
	0,52550	72	4,0	1				

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
celkem			415,8	8				
T3-1	0,01540	138	13,2	1				
	0,05100	140	66,0	1				
	0,51500	139	6,9	1				
celkem			86,1	3				
T3-2	0,89500	145	13,5	1				
	0,15100	146	59,8	1				
celkem			73,3	2				
T4-1	0,03900	152	43,7	1				
	0,04600	153	22,3	1				
celkem			66,0	2				
T4-3	0,11250	71	11,9	1				
	0,11300	70	20,8	1				
celkem			32,7	2				
celkem SO 02 Dolní Rychnov			3047,2	93	5,0	1	0	
TH	0,03160	158	40,4	1				
	0,07220	68	52,0	1				
	0,12000	67	60,8	1				
	0,13675	66	32,3	1				
	0,16750	65	45,0	1				
	0,17000	160	79,7	1				
	0,18720	64	39,0	1				
	0,20950	161			6,0	1		
	0,24350	162	24,7	1				
	0,40400	53	54,3	1				
	0,57200	219+220+ 205+166			16,2			2xBD+MŠ+u 1 bytovna
	0,57870	167	5,2					zaslepeno
	0,97230	200	4,4	1				
	0,69600	168	16,5	1				
	0,72150	169	23,5	1				
	0,77660	170	35,2	1				
	0,82740	171	11,4	1				
	0,84930	172	25,0	1				
	0,91620	p.č.1183	39,5					zaslepeno
	0,91670	174	92,6	1				
	0,95460	33	20,4	1				
	0,98870	222	49,2	1				
	1,04370	31	26,2	1				
	1,09220	176	67,2	1				
	1,13040	177	19,4	1				
	1,23360	179	15,3	1				pojezdny poklop
	1,27500	180	12,0	1				
	1,43200	24	17,8	1				
	1,45800	184	7,5	1				

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
	1,52030	185	19,2	1				
	1,58120	18	8,5	1				
	1,59400	186	13,7	1				
	1,61530	187	16,8	1				
	1,64930	188	25,6	1				
	1,73000	14	27,5	1				
	1,79150	189	54,7	1				
	1,82200	190	43,2	1				
	1,87120	11	30,6	1				
	1,95470	223	7,0	1				
	1,98940	10	57,0	1				
	2,10800	193	66,6	1				
	2,10850	191	76,8	1				
	2,20900	192	14,5	1				
	2,21150	212	58,0	1				
	2,21200	9	60,7	1				
celkem			1496,9	41	22,2	1	1	
T5	0,04830	73	22,4	1				
	0,05220	197	56,1	1				
	0,06650	69	21,8	1				
celkem			100,3	3				
T6	0,02430	55			17,1	1		BD
	0,02480	54	37,7	1				
	0,03950	63	22,2	1				
	0,08140	59	6,3	1				
	0,10100	58	69,6	1				
	0,13450	206	8,5	1				
	0,15600	57	14,8	1				
	0,15650	56	62,0	1				
celkem			221,1	7	17,1	1		
T6-1	0,04660	60	7,5	1				
	0,56800	61	18,5	1				
	0,06000	62	13,3	1				
	0,16450	221	3,9	1				
celkem			43,2	4				
T7	0,10270	42	24,2	1				
	0,15380	43			4,2	1		BD
	0,22400	194	26,8	1				
	0,22450	44	56,8	1				
celkem			107,8	3	4,2	1		
T7-1	0,02600	47	18,4	1				
	0,05610	46			81,0	1		
	0,05660	49	49,5	1				
	0,05710	48	20,8	1				
	0,06820	52			68,2	1		BD
	0,09900	51	4,5	1				
	0,10050	50	4,5	1				

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
celkem			97,7	5	149,2	2		
T7-2	0,02800	164	20,8	1				
	0,02850	163	17,8	1				
celkem			38,6	2				
T8	0,03500	38	8,0	1				
	0,14150	39	142,0	1				
celkem			150,0	2				
T9-1	0,01200	37	12,0	1				
	0,02750	230	39,3	1				
celkem			51,3	2				
T9-2	0,02450	34	20,4	1				
celkem			20,4	1				
T9-3	0,02800	203	50,9	1				
	0,04800	175	19,5	1				
	0,04850	30	27,8	1				
	0,07550	173	4,5	1				
celkem			102,7	4				
T9-4	0,04060	28	25,0	1				
	0,05120	29	32,7	1				
	0,15130	p.č.2034/2	15,2	1				
	0,20600	p.č.2034/1	48,6	1				
	0,26650	232	10,7	1				
celkem			132,2	5				
T10	0,04050	27	11,2	1				
celkem			11,2	1				
T10-1	0,03500	26	26,5	1				
	0,08950	25	8,6	1				
celkem			35,1	2				
T10-2	0,04250	182	7,7	1				
	0,06800	181	30,5	1				
	0,06850	183	54,0	1				
celkem			92,2	3				
T11	0,08250	15	7,7	1				
	0,15500	16	64,3	1				
	0,37450	13	9,0	1				
celkem			81,0	3				
T11-1	0,04550	17	6,5	1				
	0,04750	19	5,7	1				
celkem			12,2	2				
T11-2	0,10200	20	20,2	1				
	0,12470	23	82,5	1				
	0,14650	21	8,6	1				
celkem			111,3	3				
T12	0,06450	228	56,3	1				
	0,10100	8	11,8	1				
	0,21000	7	8,2	1				
	0,26000	6	33,0	1				

STOKA	STANIČENÍ	ČP	PE D40 (m)	DČJ 1,0m (ks)	PE D50 (m)	DN1200 (ks)	DN1500 (ks)	poznámka
	0,27250	217+5	100,0	1				
	0,27300	3+4	158,2	1				
	0,38900	1	114,0	1				pojezdňý poklop
	0,39550	2	29,7	1				
celkem			511,2	8				
celkem SO 03 Horní Rychnov			3416,4	101	192,7	5	1,0	