

Výpis materiálu

Autor: Ing. Martin KOPTA				Datum: 15.10.2019			Strana: 1		
Název: SKLUZ DÉLKY 30 m							Číslo výkr. 089-19-001		
Pos.	Specifikace polotovaru						Hmotnost		
	Počet [ks]	Jméno	Šířka [mm]	Délka [mm]	Materiál	Norma	[kg/MJ]	[kg/ks]	[kg/soubor]
1	1	TR KR 273 x 6.3		30500.00	S 235	ČSN 42 5715	41.45	1264.23	1264.23
2	3	PR 4HR		1350.00	S 235	ČSN 42 6935	8.29	11.19	33.57
3	3	PR 4HR		194.00	S 235	ČSN 42 6935	8.29	1.61	4.82
4	6	PR 4HR		1200.00	S 235	ČSN 42 6935	8.29	9.95	59.69
5	6	PR 4HR		150.00	S 235	ČSN 42 6935	8.29	1.24	7.46
6	6	PR 4HR		850.00	S 235	ČSN 42 6935	8.29	7.05	42.28
7	6	PR 4HR		50.00	S 235	ČSN 42 6935	8.29	0.41	2.49
8	15	P 10	150.00	200.00	S 235	ČSN 42 5310	80.00	2.40	36.00
9	6	P 10	100.00	350.00	S 235	ČSN 42 5310	80.00	2.80	16.80
10	18	KR 24		5200.00	S 235	ČSN 42 5510	3.55	18.46	332.28
11	5	P 6	505.00	6000.00	400 HB	ČSN 42 5310	48.00	145.44	727.20
12	60	P 6	135.00	273.00	400 HB	ČSN 42 5310	48.00	1.77	106.14
13								0.00	0.00
14								0.00	0.00
15								0.00	0.00
16								0.00	0.00
17								0.00	0.00
18								0.00	0.00
19								0.00	0.00
20								0.00	0.00
21								0.00	0.00
22								0.00	0.00
23								0.00	0.00
24								0.00	0.00
25								0.00	0.00
26								0.00	0.00
27								0.00	0.00
28								0.00	0.00
29								0.00	0.00
30								0.00	0.00
31								0.00	0.00
32								0.00	0.00
33								0.00	0.00
34								0.00	0.00
35								0.00	0.00
36								0.00	0.00
37								0.00	0.00
38								0.00	0.00
39								0.00	0.00
40								0.00	0.00
POZNÁMKA:									
Označení materiálu 400 HB odpovídá jakosti ořezávací oceli jmenovité tvrdosti 400 HB.									
Hmotnost celkem:								2 632.96	