





D.










13"x43" optics
(Clark 2.6)




13"x43" optics
(Clark 2.7)









POWER / POWER SUPPLY CODE	5W 24Vdc CK26001 B White CK26001 N Black
LED COLOUR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 11" M - 17" P - 19" sharp L - 32" J - 65" W - 13"x43"
LUMEN OUTPUT AT SOURCE	452 lm (3000K)
DELIVERED LUMEN OUTPUT	303 lm (3000K, 32")
NO. AND TYPE OF LEDS	1 high-intensity power LED
MATERIAL	body and trim in aluminium
POWER SUPPLY UNIT	not included, see p. 36
POWER CABLES	includes 1.5 m PVC cable FROR 2x0.35/0.35 Ø3.5 mm
MOUNTING	recessed (ceiling, shelf, shop window)
FEATURES	CRI 90

POWER / POWER SUPPLY CODE	5W 24Vdc CK27001 B White CK27001 N Black
LED COLOUR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 11" M - 17" P - 19" sharp L - 32" J - 65" W - 13"x43"
LUMEN OUTPUT AT SOURCE	452 lm (3000K)
DELIVERED LUMEN OUTPUT	303 lm (3000K, 32")
NO. AND TYPE OF LEDS	1 high-intensity power LED
MATERIAL	body and trim in aluminium
POWER SUPPLY UNIT	not included, see p. 36
POWER CABLES	includes 1.5 m PVC cable FROR 2x0.35/0.35 Ø3.5 mm
MOUNTING	recessed (ceiling, shelf, shop window)
FEATURES	CRI 90